

richpos

3500 series



A powerful touchscreen POS system of its class, the RichPOS3500 is suitable for any hospitality and specialty retail environments. The touchscreen allows easy interactivity for users and delivers accurate input. Its low-voltage and low-power consumption processor gives way for 24/7 operation. Thanks to its plug-in/out design, this sleek POS system's slide-in design can be easily removed and is easy to maintain. Constructed from aluminum die-cast, with the integration of plexi-glass on the front bezel, this powerful, modularized P4 POS system, is dedicated for high performance and high intensity workload.

Features

- ▣ Delivers unsurpassed performance with its Pentium 4 platform
- ▣ Touchscreen POS that facilitates user interactivity
- ▣ Die-cast aluminum housing, with integrated plexi-glass front bezel
- ▣ Easy maintenance with the system's plug-in/out design



richpos
3500 series

Model	RP-3515
Platform	Pentium 4
Processor	Intel Ultra Low Voltage Celeron-M 1GHz (Embedded on board)
Memory	256MB standard, maximum 1GB (1 x 200-pin DDR SODIMM)
Touch LCD Display	
Size / Resolution	15" TFT LCD / 1024 x 768
Brightness	250 ~ 350 cd/m ²
Touch Screen	ELO 5-wire Resistive/Fujitsu 4-wire Resistive
I/O Connectivity	
Serial Port	<ul style="list-style-type: none"> • 4 x External: COM1, COM2, COM5, COM6 (D-Sub) • 2 x Internal: COM3 for Primary Touchscreen, COM4 (RJ11) for VFD
Parallel Port	1 x Parallel
USB port (standard)	6 x USB 2.0 (4 x external, 2 x internal)
Cash Drawer port	1 x 12V RJ12 (12V)
Mouse port	N/A
Keyboard port	1 x PS/2 keyboard
LAN port	1 x RJ45 10/100 Base-T
VGA port	1 x VGA
Audio port	1 x Line-out, 1 x Mic-in
IDE Hard Disk Drive	Built-in 2.5" type
Compact Flash	CF socket onboard
Power Supply	150W External Power Adapter
Construction	Aluminum Die-casting Housing
Housing Color	Black / Silver
O/S Supported	Win2000, XP (Pro, Embedded), WEPOS
Dimensions (W x H x D)	375 x 390 x 255 mm
Weight	7.5 Kgs
EMI/Safety	CE, FCC, UL, RoHS
Operating Temperature	0°C ~ 35°C
Optional Peripherals	
Magnetic Stripe Card Reader	Integrated MCR Single/Dual/Triple Track
MCR 2-in-one / MCR 3-in-one	Integrated MCR+RFID, MCR+fingerprint 12.1" / 8.4" TFT LCD (Resistive Touch/Non-touch)
Customer Pole Display	Integrated VFD / LCD Customer Pole Display
Wireless LAN	Integrated 802.11b/g Wireless LAN Module (USB interface)

All product specifications are subject to change without notice. V0702

FEC

FIRICH ENTERPRISES CO., LTD.
10F, No.75, Sec. 1, Sin Tai Wu Rd., Sijhih City,
Taipei County 221, Taiwan R.O.C.
tel 886-2-2698 1446 fax 886-2-2698 1451

Firich China-Crisom
Room 1508, No. 818, Nanjing West Road,
JingAn District, Shanghai City, China
Post Code: 200041
tel 86-21-51096766 fax 86-21-51096766

Firich Korea Inc.
506 DAERUNGTECHNOTOWN
8th Kasan-dong, 481-11 Geumcheon, Seoul, Korea
tel 82-2-8376610 fax 82-2-8376070
www.firich.co.kr

Firich USA Inc.
380 Fairview Way, Milpitas, CA 95035, USA
tel 408-942-7043 fax 408-942-7143
sales@firichusa.com
www.firichusa.com